

D 90



FROZEN DICE



Self-contained ice dispenser - Sprayer system
Daily production up to 48 kg

• Position n°




• Application fields

Hotel	●●●●●●●●●●	Fish market	●●●●●●●●●●
Restaurant	●●●●●●●●●●	Supermarket	●●●●●●●●●●
Fast food	●●●●●●●●●●	SPA	●●●●●●●●●●
Bar	●●●●●●●●●●	Medical	●●●●●●●●●●
Disco	●●●●●●●●●●	Industry	●●●●●●●●●●

• Features & Plus

- Full cube, compact and crystalline
- Ice cubes dispenser
- External structure AISI 304 Scotch Brite
- Electromechanical functioning
- Air Cooling and Water Cooling systems
- Internal bin insulation HCFC free
- Easy cleaning thanks to rounded surfaces
- Conformity to RoHS directive
- Standard and special voltages
- Model in Tropical Class + 43 ° C

• Available dice size



• Prod. 24h

Air temp.	Water temp.	Prod. 24h kg
10° C	10° C	48
21° C	15° C	44
32° C	21° C	40

2 Years Warranty

subject to limitations

• Certifications available for this model



www.ntfice.it
info@ntfice.it



ntfice.it




D 90



FROZEN DICE



Self-contained ice dispenser - Sprayer system
Daily production up to 48 kg



• Connections

All measures are referred to the rear bottom-left corner (L-H-Ø)

- ① Water inlet:
111 mm - 311 mm - 3/4"
- ② Water outlet:
49 mm - 270 mm - 24mm
- ③ Electrical connection:
156 mm - 347 mm

• Working conditions





- Location: Indoor

	Min	Max
Ambient temperature	+10° C	+43° C
Water temperature	+3° C	+32° C
Voltage	-10%	+10%
Water inlet pressure	1bar (14 psi)	6bar (84 psi)

• Technical information

Production in 24h	44 kg
Store capacity, up to	12 kg
Cooling system	A - W
Kind of cube	14 g
Refrigerant	R404A - R452A
Standard voltage	220-240 V ~ 50 Hz
Electrical consumption	450 W
Fuse	10 A
Water consumption	A: 4 l/kg W: 15 l/kg
Delivered ice	3 kg/min
Sizes (L-P-H mm)	500 - 630 - 920
Sizes with pack (L-P-H mm)	540 - 770 - 1090
Net weight	66 kg
Gross weight	74 kg
Finish	AISI 304 stainless steel, scotch brite

All the technical information must be considered at the following conditions:

			
Standard Cube (14 g)	Ambient temperature +21° C	Water temperature +15° C	Electrical consumption at +43° C (standard voltage)

Models and specifications are subject to change without notice
Rev. 02 - Issued September 2019



www.ntfice.it
info@ntfice.it



ntfice.it

