



MULTI PURPOSE OVENS



Modular Design

- * A wide range of option to choose from. Single, Double, Tripple deck options with or without fermentation cabinets and benches.
- * You can start small with one deck and work your way up to 3 decks as your business grows.
- * Independent Control and Wiring for Each Deck
- * Modular design makes it easier to re-locate the oven.

User-Friendly Control Panel

- * Precise Heat Control
- * In-Built Timer
- Turbo-mode for meeting daily challenges and operations
- * The Electronic Panel is cooled and well-insulated making it durable.
- * Temperatures reaching up to 400 Centigrad Degrees

Heat Consistency and Utmost Control

- * Front/ rear upper and lower heating elements are controlled seperately.
- * Upper Heating Elements are placed in ceramic tubes for the heat consistency.
- * 90 mm insulation and Italian-made claystones making sure that the oven is heat-consistent and energy efficient.

Options

- * Fullstone option for the maximum heat consistency and insulation.
- * Steam Option for wider range of applications .

Design

- * Bottom Opening Door
- * Double in-door lights per deck
- * Doors are equipped with heat-isolating glass.
- * Robust Legs with caster wheels

Applications

- * Pizza, Breads, Baklava, Bakery and Pastry products.

TECHNICAL SPECIFICATIONS

MODEL	MT-800-2	MD-800-2	MD-800-1	ME 800
EXTERIOR DIMENSIONS (x-y-z cm)	126 X 102 x 205	126 x 102 x 185	126 x 102 x 185	126 x 102 x 40
INTERNAL DIMENSIONS (X-y-z cm)	3 PIECES 84 x 84 x 18	2 PIECES 84 x 84 x 18	2 PIECES 84 x 84 x 18	1 PIECE 84 x 84 x 18
TOTAL ELECTRIC POWER (KW)	25,5 KW (with Steam System-29,7KW)	18 KW (with Steam System-20,8KW)	15 KW (with Steam System-17,8KW)	7,5 KW (with Steam System-8,9KW)
POWER SUPPLY VOLTAGE (V)	380-400 V 3 NPE	380-400 V 3 NPE	380-400 V 3 NPE	380-400 V 3 NPE
OPERATING FREQUENCY (Hz)	50/60	50/60	50/60	50/60
THERMOSTAT RANGE (°C)	50-400	50-400	50-400	50-400
POWER CORD mm (H07 RNFR)	5 x 6	5 x 6	5 x 6	5 x 4
PROTECTION CLASS	IP 20	IP 20	IP 20	IP 20
NET WEIGHT (KG)	498 (with Steam System-543kg)	383 (with Steam System-413kg)	355 (with Steam System-385kg)	130 (with Steam System-145kg)
RATED CURRENT (A)	100	75	50	25
INSULATION	ROCK WOOL	ROCK WOOL	ROCK WOOL	ROCK WOOL
COOKING STONE	FIRECLAY STONE	FIRECLAY STONE	FIRECLAY STONE	FIRECLAY STONE
LIGHTING	6 PIECES 25 W	4 PIECES 25 W	4 PIECES 25 W	2 PIECES 25 W
CAPACITY(CM) (PER FLOOR)	40x80x2 Pieces 40x60x2 Pieces 40x40x4 Pieces Ø 40x4 Pieces	40x80x2 Pieces 40x60x2 Pieces 40x40x4 Pieces Ø 40x4 Pieces	40x80x2 Pieces 40x60x2 Pieces 40x40x4 Pieces Ø 40x4 Pieces	40x80x2 Pieces 40x60x2 Pieces 40x40x4 Pieces Ø 40x4 Pieces

TECHNICAL SPECIFICATIONS

MODEL	MT-1200-2	MD-1200-2	MD-1200-1	ME-1200_1	ME 1200
EXTERIOR DIMENSIONS (x-y-z cm)	166 x 102 x 205	166 x 102 x 185	166 x 102 x 185	166 x 102 x 165	166 x 102 x 40
INTERNAL DIMENSIONS (X-y-z cm)	3 PIECES 124 x 84 x 18	2 PIECES 124 x 84 x 18	2 PIECES 124 x 84 x 18	1 PIECE 124 x 84 x 18	1 PIECE 124 x 84 x 18
TOTAL ELECTRIC POWER (KW)	34,5 KW (with Steam System-43,5KW)	24 KW (with Steam System-30KW)	21 KW (with Steam System-27KW)	10,5 KW (with Steam System-13,5KW)	10,5 KW (with Steam System-13,5KW)
POWER SUPPLY VOLTAGE (V)	380-400 V 3 NPE	380-400 V 3 NPE	380-400 V 3 NPE	380-400 V 3 NPE	380-400 V 3 NPE
OPERATING FREQUENCY (Hz)	50/60	50/60	50/60	50/60	50/60
THERMOSTAT RANGE (°C)	50-400	50-400	50-400	50-400	50-400
POWER CORD mm (H07 RNFR)	5 x 10	5 x 6	5 x 6	5 x 4	5 x 4
PROTECTION CLASS	IP 20	IP 20	IP 20	IP 20	IP 20
NET WEIGHT (KG)	660 (with Steam System-727,5kg Fullstone-810kg)	505 (with Steam System-550kg Fullstone-605kg)	455 (with Steam System-500kg Fullstone-555kg)	290 (with Steam System-312,5kg Fullstone-340kg)	170 (with Steam System-192,5kg Fullstone-220kg)
RATED CURRENT (A)	121	89	64	32	32
INSULATION	ROCK WOOL	ROCK WOOL	ROCK WOOL	ROCK WOOL	ROCK WOOL
COOKING STONE	FIRECLAY STONE	FIRECLAY STONE	FIRECLAY STONE	FIRECLAY STONE	FIRECLAY STONE
LIGHTING	6 PIECES 25 W	4 PIECES 25 W	4 PIECES 25 W	2 PIECES 25 W	2 PIECES 25 W
CAPACITY(CM) (PER FLOOR)	40x80x3 Pieces 40x60x4 Pieces 40x40x6 Pieces Ø 40x6 Pieces	40x80x3 Pieces 40x60x4 Pieces 40x40x6 Pieces Ø 40x6 Pieces	40x80x3 Pieces 40x60x4 Pieces 40x40x6 Pieces Ø 40x6 Pieces	40x80x3 Pieces 40x60x4 Pieces 40x40x6 Pieces Ø 40x6 Pieces	40x80x3 Pieces 40x60x4 Pieces 40x40x6 Pieces Ø 40x6 Pieces