



**Catalogue**  
**CATERING**  
**Chapter**  
**REFRIGERATION**

**Model**

19048328

01/03/2019

**WINE DISPLAY CABINETS, WR-600**


**SPECIFICATIONS**

Pre-lacquered steel outside. Sanitary thermoformed plastic inside with embedded inner tray slides (polystyrene).  
 45 mm, 40 kg/m<sup>3</sup> injected polyurethane isolation.  
 Forced draught cooling system with low vibration compressor.  
 Inner evaporator with forced draught. Outer low maintenance condenser with forced draught.  
 Digital display for electronic and digital control of temperature and defrosting.  
 Double pane door with tinted glass and UV filter for sunlight protection.  
 Black plastic covered steel grid removable shelves for easy cleaning.  
 Equipment: 3 flat shelves and 1 tipped shelf for main bottles or the conservation of opened bottles (models WR-300/600) one flat unit for model WR-180.  
 LED vertical lighting system.  
 Working temperature: +5 °C, +16 °C (Room temperature: 32 °C).

Doors: 2  
 Capacity: 800 L  
 Bottle capacity: 144

**DIMENSIONS**

X Width	1240 mm	X Gross width	1300 mm
Y Depth	655 mm	Y Gross depth	675 mm
Z Height	1850 mm	Z Gross height	1965 mm
Net Weight	188,0 kg	Gross Weight	206,0 kg
Net volume	1,503 m <sup>3</sup>	Gross volume	1,724 m <sup>3</sup>



**ELECTRICITY TECHNICAL SPECIFICATIONS**

Electric power	0,513 kW
Voltage	230V - 1N
Amperage	3,6A
Electric frequency	50/60Hz

**GAS TECHNICAL SPECIFICATIONS**

Gas type	R-134a
----------	--------

**COLD TECHNICAL SPECIFICATIONS**

Refrigeration power	0,508 kW
Climate class	4
Cooling gas load	185,000 g

**UNDARTAKEN TECHNICAL SPECIFICATIONS**

Single-phase 230V wiring	1+N
--------------------------	-----



01/03/2019

