



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CCP-4G HHHH 230V 1N 50Hz

19089574

10/02/2023

The photo may show the standard model and not the configured one

DENOMINATION:

Refrigerated counter with drawers - Concept 700 Gastronorm with 4 doors (3H+1D).

DESCRIPTION :

- Structure built with AISI-304 stainless steel
 - 50 mm, 40 kg/m3 injected polyurethane insulation.
 - Forced draught cooling system inside the room.
 - Copper piping and aluminium flaps evaporator.
 - Digital display for electronic and digital control of temperature and defrosting.
 - The controls are integrated in the front panel for a better protection against dirt. IPX5 compliant, the controls are protected against water splash and jets.
 - Easier loading and unloading thanks to its door self-closing and stay open features.
 - Removable and height adjustable plastic covered steel shelves for easy cleaning (GN1/1 size).
 - Equipment per door: 1 GN 1/1 grid and 2 sets of height adjustable tray slides.
 - Built-in drainage to get rid of waste liquids inside the unit.
 - Interior LED lighting (only for models with glass doors).
 - Embedded bottom and curved panels inside for easy cleaning and maintenance.
 - Height adjustable stainless steel legs.
 - 10 cm high splashback.
 - Working temperature: from 0 °C to +8 °C (refrigerators) and from -18 °C to -22 °C (freezers).
 - Tested in climatic class IV.
- Refrigerated counters with "H" drawers.
VERSATILITY: Different sets of drawers for the most specific requirements.
ROBUSTNESS: Our perforated stainless steel drawers can stand loads up to 40 kg.


POSSIBLE OPTIONS :

- 60 Hz
- Stainless Backing
- Wheels Kit (Factory Assembly)
- British plug
- Door frame resistance
- Granite worktop
- Left group
- Without breastplate
- Without Countertop

POSSIBLE ACCESSORIES :

- ACCESSORIES
- ACCESSORIES FOR REFRIGERATION
- GASTRONORM GRIDS

DIMENSIONS



X Width	2242 mm	X Gross width	2353 mm
Y Depth	700 mm	Y Gross depth	825 mm
Z Height	850 mm	Z Gross height	1000 mm
Net Weight	191,0 kg	Gross Weight	202,0 kg
Net volume	1,334 m3	Gross volume	1,941 m3

ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,224 kW
Amperage (A)	1,04 A
Voltage	230V - 1N
Electric frequency	50Hz

GAS TECHNICAL SPECIFICATIONS

Gas type	R-600a
----------	--------

COLD TECHNICAL SPECIFICATIONS

Refrigeration power	0,436 kW
Annual elec. consumption	1096,00 kWh
Power consumption 24h	3,00 kWh
Gross internal volume	581 L
Refrigeration net.vol	240 L
Climate class	4
Cooling gas load	108,000 g
Clasif. Energy efficiency	C
Energy Efficiency Index	45,56 %
Model Type	Counter Cabinet

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1+T-2A
--------------------------	----------

OTHERS

Number of doors	1
Condensation system	Vent.





Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CCP-4G HHHH 230V 1N 50Hz

19089574

10/02/2023

