



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CUP-12G 230V 1N 50Hz

19089446

23/03/2022

DENOMINATION:

Refrigerated cabinet - Concept Gastronorm with 2 compartments and 2 door, at 50Hz.

DESCRIPTION :

- Structure built with AISI-304 stainless steel.
 - 60 mm, 40 kg/m³ injected polyurethane insulation.
 - Embedded inner tray slides. Storage trays at 23 different levels 55 mm from each other.
 - Forced draught cooling system with hermetically sealed compressor.
 - Copper piping and aluminium flaps evaporator.
 - Digital display for electronic and digital control of temperature and defrosting.
 - Opened door delay alarm.
 - Self-closing and stay open doors. When opened less than 90° they close by themselves. When opened more than 135° they stay open.
 - Built-in drainage to get rid of waste liquids inside the unit.
 - Embedded bottom and curved panels inside for easy cleaning and maintenance.
 - Height adjustable stainless steel legs.
 - Working temperature: from 0 °C to +8 °C (refrigerators) and from -18 °C to -22 °C (freezers).
 - Tested in climatic class 4..
 - Inner LED lights with power switch (in refrigerated cabinets and now also in freezing units).
- Refrigerated cabinet

POSSIBLE OPTIONS :

- Stainless Backing
- Wheels Kit (Factory Assembly)
- British plug
- Door frame resistance
- Glass door
- Opposite Opening
- Remote group


POSSIBLE ACCESSORIES :

- REFRIGERATION
- ACCESSORIES
- GASTRONORM GRIDS

SUPPLIED ACCESSORIES:

- 12037958 GN-2/1 GRID made in Epoxi (650x530) 3

DIMENSIONS



X Width	653 mm	X Gross width	730 mm
Y Depth	842 mm	Y Gross depth	880 mm
Z Height	2040 mm	Z Gross height	2063 mm
Net Weight	152,0 kg	Gross Weight	160,0 kg
Net volume	1,122 m ³	Gross volume	1,325 m ³

ELECTRICITY TECHNICAL SPECIFICATIONS

Amperage (A)	0,9 A
Electric frequency	50Hz
Electric power	0,183 kW
Voltage	230V - 1N

GAS TECHNICAL SPECIFICATIONS

Gas type	R-600a
----------	--------

COLD TECHNICAL SPECIFICATIONS

Annual elec. consumption	548,00 kWh
Clasif. Energy efficiency	C
Climate class	4
Cooling gas load	98,000 g
Energy Efficiency Index	41,62 %
Gross internal volume	543 L
Model Type	Vertical cabinet
Power consumption 24h	1,50 kWh
Refrigeration net.vol	430 L
Refrigeration power	0,361 kW

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1+T-2A
--------------------------	----------

OTHERS

Condensation system	Vent.
Number of doors	2





Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CUP-12G 230V 1N 50Hz

19089446

23/03/2022

