



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
 CCPB-3G W NS 230V 1N 50Hz

19089605

30/03/2022

DENOMINATION:

Refrigerated base with 2/3 drawers - Concept 700 Gastronorm with 3 doors (3x2/3), at 50Hz.

DESCRIPTION :

- Structure made of AISI-304 stainless steel.
- Height of 584 mm with worktop without bollard, suitable for mounting cooking units on its surface.
- 50 mm of injected polyurethane insulation with a density of 40 kg/m³.
- Forced draught cooling system placed inside the chamber.
- Copper tube evaporator and aluminium fins.
- Electronic and digital control of temperature and defrosting with digital display.
- The control is integrated in the front panel and is thus better protected against dirt and has the official IPX5 degree of protection against splashes and jets of water.
- Models available with doors and drawers.
- Automatic closing and locking mechanism on the doors, which helps to increase convenience when loading and unloading equipment.
- Plastic-coated steel shelves easily removable for cleaning with height adjustable runners (size GN1/1).
- Integrated drainage by means of a recessed drainage system that allows the evacuation of any waste water that may be produced inside the unit.
- Deep-drawn base and curved interior for easy cleaning and storage.
- Height adjustable stainless steel legs.
- Working temperature: 0 °C, +8 °C (refrigerators).
- Tested in climatic class IV.

POSSIBLE OPTIONS :

- Stainless Backing
- Wheels Kit (Factory Assembly)
- British plug
- Door frame resistance
- Without Countertop

STANDARD OPTIONS :


- Without breastplate
- Drawers [1/3 + 2/3] unit

POSSIBLE ACCESSORIES :

- ACCESSORIES
- GASTRONORM GRIDS

DIMENSIONS

X Width	1792 mm	X Gross width	1910 mm
Y Depth	700 mm	Y Gross depth	825 mm
Z Height	584 mm	Z Gross height	765 mm
Net Weight	139,0 kg	Gross Weight	146,0 kg
Net volume	0,733 m ³	Gross volume	1,205 m ³



ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,203 kW
Amperage (A)	0,96 A
Voltage	230V - 1N
Electric frequency	50Hz

GAS TECHNICAL SPECIFICATIONS

Gas type	R-600a
----------	--------

COLD TECHNICAL SPECIFICATIONS

Refrigeration power	0,361 kW
Annual elec. consumption	931,00 kWh
Power consumption 24h	2,55 kWh
Gross internal volume	277 L
Refrigeration net.vol	121 L
Climate class	4
Cooling gas load	64,000 g
Clasif. Energy efficiency	C
Energy Efficiency Index	44,34 %
Model Type	Counter Cabinet

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1+T-2A
--------------------------	----------

OTHERS

Condensation system	Vent.
---------------------	-------



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CCPB-3G W NS 230V 1N 50Hz

19089605

30/03/2022

